

MT-8006B Data Diver



PBX Pause



Hands-free



Tone & Pause



Polarity Test



Last Number Redial

Test Equipment Depot

 1-800-517-8431

99 Washington Street
 Melrose, MA 02176
 Phone 781-665-1400
 Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com



LCD display w/ backlight

LCD display with backlight function allows for data reading in dark areas

Talk / Monitor

High impedance monitor for data safe operation without disrupting existing traffic

Polarity indication

Identify the telephone line polarity easily

Smart power saving

Smart power saving enables battery life up to 6 months

Hands-Free

Headset provides convenient hands-free function



Headset provides convenient hands-free function



Telephone line testing



High impedance monitor



Accessories

| ELECTRICAL | |
|-------------------------|--|
| Loop limit | 2 KΩ maximum at 48 Vdc (nominal 20 mA minimum loop current) |
| DC resistance | |
| Talk Mode | 300Ω typical |
| Monitor impedance | >39kΩ nominal at 1 KHz |
| Rotary dial output | |
| Pulsing rate | 10pps+0.8pps |
| Percent break | 60/40%±2% |
| Inter digit interval | 1000 ms typical |
| Leakage during Break | >130 KΩ |
| DTMF output | |
| Tone frequency error | ±1.5% maximum |
| Tone level | -8±2dBm combined (typical) |
| High versus low tone | 4 dB maximum |
| Memory dialing | |
| Memory capacity | 12 memories |
| Digit capacity | 16 digits per memory |
| PBX pause duration | 1~3.6 seconds |
| Power source | 4pcs 1.5V AAA batteries (not included) |
| PHYSICAL(Hook included) | |
| Measurement | 218.5 × 69.5 × 49mm (8.6" × 2.7" × 1.9") |
| Weight | 208g typical |

Picture for reference only. Please check with distributor for exact offers. All specifications are subject to change without notice.

Pro'sKit®

